PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION International Bureau



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6:

D03D 9/00, A41D 31/00, F41H 5/04

(11) International Publication Number:

WO 98/45516

1,,

A1

(43) International Publication Date:

15 October 1998 (15.10.98)

(21) International Application Number:

PCT/GB98/01028

(22) International Filing Date:

7 April 1998 (07.04.98)

(30) Priority Data:

9707016.3

7 April 1997 (07.04.97)

GB

(71) Applicant (for all designated States except US): SOAR ENGINEERING LTD. [GB/GB]; Beaumont Road, Banbury, Oxfordshire OX16 7SD (GB).

(72) Inventor; and

(75) Inventor/Applicant (for US only): SOAR, Richard, Kenneth, Henry [GB/GB]; The Manor House, Coleworth, Near Banbury OX17 2BB (GB).

(74) Agent: SHAW, Laurence; Laurence Shaw & Associates, Metropolitan House, 5th floor, 1 Hagley Road, Edgbaston, Birmingham B16 8TG (GB). (81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).


Published

With international search report.

(54) Title: PROTECTIVE MATERIAL

(57) Abstract

A protective material suitable for use as body armour, able to withstand penetration by a pointed weapon such as a dagger, is made from twisted multi-strand cable woven into a lattice having interstices, each cable comprising strands grouped in sets; the strands of the sets and the sets of the cable being twisted in opposite directions.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav	TM	Turkmenistan
BF	Burkina Faso	GR	Greece		Republic of Macedonia	TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malaw i	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands YU		Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	zw	Zimbabwe
CI	Côte d'Ivoire	KР	Democratic People's	NZ	New Zealand		
CM	Cameroon		Republic of Korea	PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

1

PROTECTIVE MATERIAL

The invention relates to protective material useful as body armour of the sort to be worn for security purposes. More particularly it is an object of the invention to provide body armour material which can withstand attack by a sharp weapon such as a dagger and resist other forms of assault.

In one aspect the invention provides a stab-resistant flexible lightweight mesh comprising lengths of multi-strand cable woven together into a lattice having interstices, each length overlying the length substantially at right angles to it, the lengths being spaced such that they co-operate to resist movement apart when the tip of a stab weapon is urged into the interstice, whereby the interstice tends to maintain its integrity.

Because of the structure of the wires, the network or mesh is relatively flexible. The reverse twist of sets within a wire, provides strength and flexibility. Preferably the network is dimensioned so that the wires are close together so that the interstices in between are small. As a result of the woven nature of the wires an attempt to insert a knife through the network will fail. An attempt to cut the mesh will be resisted by the flexibility of the wires. The force of a direct blow will be deflected leaving little or no trauma damage.

Preferably the network or mesh is a relatively open weave say 14 meshes per linear inch or

12 meshes per linear inch. The number of strands making up each wire may vary widely

according to need.

Preferably the strands are formed of high tensile carbon steel or stainless steel, optionally

plated for example brass plated.

The network or mesh may be arranged so that one layer will suffice, preferably two layers

are present one above the other to ensure that a jacket or the like made of the material is

impregnable.

Material of the invention may be used for a variety of uses for example in body vests,

protection panels for groin, arm or leg and the like; fencing; as curtains or shields on

vehicles; as anti-mine protection for boots; and the like. The material may be joined, e.g.

stitched to one or more layers of cotton, KEVLAR and the like, to form a unitary material.

In order that the invention may be well understood it will now be described by way of

example with reference to the accompanying diagrammatic drawings in which:

Figure 1 is a plan view of woven mesh of the invention;

3

Figure 2 is a side elevation partly in section of one interstice drawn to an enlarged scale; and

Figure 3 shows the detail of an individual wire.

The mesh is made up of woven lengths of wire, each made up of strands and according to Figure 3. The wires are arranged in a lattice, having warps A1,A2,A3 An, and wefts B1,B2,B3Bn., defining interstices I of generally square shape.

Because of the weaving the mesh is not rectilinear as seen in elevation, but one wire bends over the other, i.e. as shown in Figure 2, the wire B1 bends over wire A1 and under wire A2. As a result the side walls of each interstice I have an upward ramp portion.

Each wire is made of sets of strands S1,S2,S3Sn, of high tensile material such as a carbon steel or stainless steel. As shown in Figure 3, each set comprises three strands wound or twisted together in a helix in one direction using ordinary lay (also called reverse lay) pattern; i.e. the three sets are wound together in the opposite direction. The number of sets and the number of strands in each set may be varied according to need.

When the blade K of a knife is urged towards the vest, in say a stabbing action, the tip of the blade will be urged into an interstice I. As the blade moves forward it will try to urge the walls of the interstice apart. Because the warps and wefts are interwoven, each side

length of an interstice must ride up the ramp of the length at right angles to it; this resistance increases as the blade penetrates (or tries to penetrate) deeper into the vest. As a result the lattice maintains its integrity even though the interstice may increase slightly in cross-sectional area. The nature of the strands tends to blunt the blade, (to the extent that, in tests, resharpening is necessary). Depending on the materials chosen the article may also be bullet proof.

The mesh may be used to make jackets and other protection for police, security guards and persons who may be engaged in armed combat, dog handlers; for body wear for example in sports play as in ball and bat games and diving; work where knives are used, e.g. cutting of meat; in transport as in jackets for motorcyclists; vehicle panels; fencing and like security devices and structures.

CLAIMS

- 1. A stab-resistant flexible lightweight mesh comprising lengths of multi-strand cable woven together into a lattice having interstices, each length overlying the length substantially at right angles to it, the lengths being spaced such that they co-operate to resist movement apart when the tip of a stab weapon is urged into the interstice, whereby the interstice tends to maintain its integrity.
- 2. A mesh according to Claim 1, wherein the cable comprises strands arranged in sets, the sets being twisted together.
- 3. A mesh according to Claim 2, wherein the strands making up each set are twisted together in a hand opposite to that by which the sets are twisted together.
- 4. Fencing comprising a mesh according to any of Claims 1 to 3.
- 5. A curtain or shield or panel for a vehicle comprising a mesh according to any of Claims 1 to 3.
- 6. Stab resistant covering incorporating a layer of mesh according to Claims 1 to 3.
- 7. A covering according to Claim 6, comprising an article for body protection




FIG. 1





FIG. 2



INTERNATIONAL SEARCH REPORT

			10 90/01020	
A. CLASSI IPC 6	IFICATION OF SUBJECT MATTER D03D9/00 A41D31/00 F41H5/04			
According to	o International Patent Classification(IPC) or to both national classifica	ation and IPC		
B. FIELDS	SEARCHED			
Minimum do IPC 6	ocumentation searched (classification system followed by classification D03D A41D F41H	n symbols)		
Documenta	tion searched other than minimumdocumentation to the extent that so	uch documents are included in the	fields searched	
Electronic d	lata base consulted during the international search (name of data bas	se and, where practical, search ter	ms used)	
C. DOCUM	ENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document, with indication, where appropriate, of the rele	evant passages	Relevant to claim No.	
P,X	WO 97 27769 A (BEKAERT) 7 August see the whole document	1997	1-7	
Α	DE 31 01 003 A (REUTLINGER) 29 Ju see the whole document	ıly 1982	1,2,4,5	
Α	DE 37 11 837 C (GRAMMER) 25 Febru	iary 1988		
Α	DE 30 23 990 A (ACKERMANN) 21 Jar	nuary 1982		
Α	US 5 062 161 A (SUTTON) 5 November	er 1991		
Α	FR 2 663 412 A (GENERAL ELECTRIC) December 1991	20		
Furti	her documents are listed in the continuation of box C.	X Patent family members a	re listed in annex.	
Special ca	stegories of cited documents :	"T" later document published after	r the international filing date	
	ent defining the general state of the art which is not lered to be of particular relevance	or priority date and not in cor cited to understand the princ	nflict with the application but	
	document but published on or after the international	invention "X" document of particular relevan		
"L" docume	ont which may throw doubts on priority claim(s) or is cited to establish the publicationdate of another		en the document is taken alone	
citatio	n or other special reason (as specified) ent referring to an oral disclosure, use, exhibition or		live an inventive step when the	
other i	means ent published prior to the international filing date but nan the priority date claimed		one or more other such docu- ing obvious to a person skilled	
	actual completion of the international search	Date of mailing of the internat	 	
1	5 July 1998	23/07/1998		
Name and r	nailing address of the ISA	Authorized officer		
	European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl, Fax: (+31-70) 340-3016	Boutelegier, C		

INTERNATIONAL SEARCH REPORT

information on patent family members

PCT/GB 98/01028

1L

	Patent document cited in search report		Publication date		tent family ember(s)	Publication date is
WO 972	7769	A	07-08-1997	AU	1442397 A	22-08-1997
DE 310	1003	Α	29-07-1982	NONE		
DE 371	1837	С	25-02-1988	FR	2613604 A	14-10-1988
DE 302	3990	Α	21-01-1982	NONE		
US 506	2161	Α	05-11-1991	NONE		
FR 266	3412	A	20-12-1991	CA CN DE GB IT JP SE US	2042198 A 1057507 A 4119858 A 2246818 A 1248610 B 4231625 A 9101844 A 5437538 A	19-12-1991 01-01-1992 19-12-1991 12-02-1992 19-01-1995 20-08-1992 19-12-1991 01-08-1995